

MACLAN RACING

MMAX8 ESC SETUP SHEET

BASIC INFORMATION

CAR & ELECTRICS

DRIVER:		CHASSIS:	
TRACK:		MOTOR:	
☐ TIGHT ☐ MEDIUM ☐ OPEN		GEARING:	
CLASS: ☐ OFFROAD ☐ ONROAD ☐			
TRACTION: ☐ LOW ☐ MEDIUM ☐ HIGH		ESC:	
SURFACE TYPE:		SERVO:	
EVENT:		BATTERY:	
DATE:			
FIRMWARE:			
SPEED CONT	R0	LLER SETTING	
GENERAL		THROTTLE	
RUN MODE: ☐ Practice ☐ Race Blinky ☐ Race Open		THROTTLE PWM:	Khz
SBEC VOLTAGE:	v		%
FORWARD POWER:	%	THROTTLE CURVE: Linear	%
REVERSE POWER:	%	DEAD BAND: %	
SENSOR MODE: ☐ Full sensored ☐ Smart Hybrid		POOCT TUDBO	
BATTERY CUTOFF: ☐ Disable ☐	v	BOOST TURBO ACCELERATION BOOST	
MOTOR TEMP. CUTOFF: ☐ Disable ☐	V	ACCEL. BOOST TIMING:	
ESC TEMP. CUTOFF: Disable	V	TURBO	
QUICK BOOT: ☐ On ☐ Off		TURBO TIMING:	
BRAKE		TURBO DELAY(sec):	
BRAKE STRENGTH:	%		
BRAKE PVM:	_Khz		
BRAKE CURVE: ☐ Linear ☐	%		
DRAG BRAKE:	%		
INITIAL BRAKE:	%		

REMARK